

Workpiece Spindle



Spingdle type	Dimensions(mm)				Spindle nose dimensions		Speed r/min	Bearings type	
	L1	L2	D1	D2	Spindle hole taper	Thorough hole			
3MK133A	355	5	130	48	Mohs 3	30	1800	7211AC/P5 x2	7211AC/P5x2
3MK133A200A000	355	5	130	48	Mohs 3	30	1800	7211AC/P4x2	7211AC/P4x2
3MK205	417	6	140	40	Mohs 3	20	1800	46211P5x2	46212P5x2
3MK1412	417	6	170	50	Mohs 4	25	1500	46214P5x2	46213P5x2
3MK3110G	362	8	190	70	----	70	3500	7020AC/P4x2	7019AC/P4x2
3MK3420	362	8	190	70	Mohs 5	65	3500	7020AC/P4x2	7019AC/P4x2
3MZ226--13	445	10	115	70	Mohs 4	20	4000	7210Ac/P5x2	7210Ac/P5x2
3MZ247A	403	6	150	75	Mohs 3	18	4000	7213AC/P4x2	7212AC/P5x2
3MZ315B	408	58	105	60	----	15	4000	7208AC/P5x2	7208AC/P5x2
3MZ3210D—02B	310	9	110	12	----	39	4000	7208AC/P5x2	7208AC/P5x2

Contact Us:

Anyang General International Co.,Ltd

Add:Suite A,4/F Jinhao Business Bld.,Renmin Rd.,Anyang,Henan,P.R.C.

Zip Code:455000

Tel: (86) 372 5965148

Fax: (86) 372 5951936

[Http://www.gcmachines.com](http://www.gcmachines.com)

E-mail: info@agico.com.cn